Evidence of Performance

Air permeability, Watertightness, Resistance to wind load

Test Report

15-001044-PR19

(PB-A01-02-en-01)

Client Europa Profil Aluminio S.A.

56th Klm National Highway

Athens - Lamia 32011 Innofita Viotas

Greece

Product Parallel sliding window

System: Europa Sliding Double Track 6000 Designation

Performance-relevant

product details

Overall dimensions

(WxH)

1600 mm x 2200 mm

Special features Test sequence were changed according to the customer re-

Aluminium profiles with thermal break

quirements

Results

Air permeability according to EN 12207:1999-11



Class 3

Watertightness according to EN 12208:1999-11



Class 2A

Resistance to wind load according to EN 12210:1999-11/AC:2002-08



Class C2 / B3

ift Rosenheim 04.05.2016

Thomas Stefan, Dipl.-Ing. (FH) Head of Testing Department Construction Product Testing

Herbert Niedermeier Operating Testing Officer **Construction Product Testing**

H. Medoures



EN 14351-1:2006+A1:2010

ROSENHEIM

Test standard/s: EN 1026:2000-06 EN 1027:2000-06 EN 12046-1:2003-11 EN 12211:2000-06 Correspond/s to the national

standard/s (e.g. DIN EN)

Representation



nstructions for use

The results obtained can be used by the manufacturer for preparing the Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EU. The provisions of the applicable product standard have to be observed.

Validity

The data and results refer solely to the tested and described specimen. Classification remains valid as long as the product and the above basis remain unchanged. The results can be extrapolated under the manufacturer's own liability subject to observance of the relevant specifications set out by the applicable product standard. This test/evaluation does not allow any statement to be made on any further characteristics regarding performance and quality of the construction presented, in particular the effects of weathering and ageing were not taken into account.

Notes on publication

The ift-Guidance Sheet "Advertising with ift test documents" applies. The cover sheet can be used as an abstract.

The report contains a total of 23 pages.



