Evidence of Performance

Air permeability, Watertightness, Resistance to wind load

Test Report No. 15-001044-PR16 (PB-A01-02-en-01)

Client	Europa Profil Aluminio S.A. 56th Klm National Highway, Athens - Lamia 32011 Innofita Viotas Greece
Product	Single tilt and turn window with fixed top light
Designation	System: Prima 8500 Multi single sash
Performance-relevant product details	Aluminium profiles with thermal break
Overall dimensions (WxH)	1,000 mm x 2,200 mm
Special features	Test sequence were changed according to the customer re- quirements

Results

Air permeability according to EN 12207:1999-11



Class 4

Watertightness according to EN 12208:1999-11

Class E1050

Resistance to wind load according to EN 12210:1999-11/AC:2002-08



Class C4 / B4

ift Rosenheim 01.02.2016

Thomas Stefan, Dipl.-Ing. (FH) Head of Testing Department Construction Product Testing

han Kertagnotto

Stephan Bertagnolli, Dipl.-Ing. (FH) Operating Testing Officer Construction Product Testing



Basis EN 14351-1:2006+A1:2010

Test standard/s: EN 1026:2000-06 EN 1027:2000-06 EN 12211:2000-06 Correspond/s to the national standard/s (e.g. DIN EN)

Representation



Instructions for use

The results obtained can be used by the manufacturer for preparing the Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EU. The provisions of the applicable product standard have to be observed. **Validity**

andrey

The data and results refer solely to the tested and described specimen. Classification remains valid as long as the product and the above basis remain unchanged. The results can be extrapolated under the manufacturer's own liability subject to observance of the relevant specifications set out by the applicable product standard. This test/evaluation does not allow any statement to be made on any further characteristics regarding performance and quality of the construction presented, in particular the effects of weathering and ageing were not taken into account.

Notes on publication

The **ift**-Guidance Sheet "Advertising with ift test documents" applies. The cover sheet can be used as an abstract.

The report contains a total of 24 pages.

ift Rosenheim GmbH K Ti Theodor-Gietl-Str. 7-9 F D-83026 Rosenheim w

Kontakt Tel. +49.8031.261-0 Fax +49.8031.261-290 www.ift-rosenheim.de

Prüfung und Kalibrierung – EN ISO/IEC 17025 Inspektion – EN ISO/IEC 17020 Zertifizierung Produkte – EN ISO/IEC 17065 Zertifizierung Managementsysteme – EN ISO/IEC 17021 PÜZ-Stelle: BAY 18

