# **Evidence of Performance**

Air permeability, Watertightness, Resistance to wind load

**Test Report** No. 15-001044-PR24 (PB-A01-02-en-01)

Europa Profil Aluminio S.A.	Basis
56th Klm National Highway	EN 14351-1:2006
Athens - Lamia 32011 Innofita Viotas Greece	Test standard/s: EN 1026:2000-06 EN 1027:2000-06 EN 12046-1:2003 EN 12211:2000-0
Double tilt and turn window	Correspond/s to the standard/s (e.g. D
System: Europa A40 SI	Representation
Aluminium profiles with thermal break	
1,600 mm x 2,200 mm	
Test sequence were changed according to the customer re- quirements	
	56th Klm National Highway Athens - Lamia 32011 Innofita Viotas Greece Double tilt and turn window system: Europa A40 SI Aluminium profiles with thermal break 1,600 mm x 2,200 mm Test sequence were changed according to the customer re-

#### Results

Client

Air permeability according to EN 12207:1999-11



# Class 4

Watertightness according to EN 12208:1999-11



### Class 8A

Resistance to wind load according to EN 12210:1999-11/AC:2002-08





ift Rosenheim 27.04.2016

Thomas Stefan, Dipl.-Ing. (FH) Head of Testing Department Construction Product Testing

Jedran Kertaghistto

Stephan Bertagnolli, Dipl.-Ing. (FH) **Operating Testing Officer** Construction Product Testing





ROSENHEIM

Dania 6+A1:2010

6 6 3-11 06 the national DIN EN)



Instructions for use

The results obtained can be used by the manufacturer for preparing the Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EU. The provisions of the applicable product standard have to be observed. Validity

The data and results refer solely to the tested and described specimen. Classification remains valid as long as the product and the above basis remain unchanged. The results can be extrapolated under the manufacturer's own liability subject to observance of the relevant specifications set out by the applicable product standard. This test/evaluation does not allow any statement to be made on any further characteristics regarding performance and quality of the construction presented, in particular the effects of weathering and ageing were not taken into account.

#### Notes on publication

The ift-Guidance Sheet "Advertising with ift test documents" applies. The cover sheet can be used as an abstract. The report contains a total of 23 pages.

ift Rosenheim GmbH Theodor-Gietl-Str. 7-9 D-83026 Rosenheim

Kontakt Tel. +49.8031.261-0 Fax +49.8031.261-290 www.ift-rosenheim.de